

# ADAX Neo WiFi

Sol\*Aire



## Overview

Stylish and modern electric panel heater with digital controls. Fully ERP LOT20 compliant.

- Programmable thermostat and timer
- In built WiFi control
- Open window detection
- Adaptive heating start
- Slimline Norwegian design
- Simple and discrete control panel

## Detail

Guarantee	5 Years (Bodywork and Electronics)
Manufacturer	ADAX
Colours	White (RAL9016) , Lava Grey

## Specs

Room Sensors	<ul style="list-style-type: none"> <li>• Electric Thermostat - accurate to (0.5 °C) range 5-35 °C.</li> <li>• Open Window Detection - activated after temperature drop of 5 degrees in 10 Min</li> </ul>
Programmer	<ul style="list-style-type: none"> <li>• 24 hour 7 day inbuilt timer</li> <li>• Assign "Comfort", "sleep" and "away" modes using the timer.</li> <li>• Create unlimited schedules</li> </ul>
Manual Control	<ul style="list-style-type: none"> <li>• Manual thermostat adjustment</li> </ul>
App Control	<ul style="list-style-type: none"> <li>• Inbuilt WiFi connectivity</li> <li>• Complete WiFi App control</li> <li>• Records energy consumption</li> </ul>
Display	<ul style="list-style-type: none"> <li>• LED digital display</li> </ul>
Eco Features	<ul style="list-style-type: none"> <li>• Open window detection</li> <li>• Adaptive heating start</li> </ul>
Installation	<ul style="list-style-type: none"> <li>• 1 H wall bracket</li> <li>• Installation template on box</li> </ul>
Protection	<ul style="list-style-type: none"> <li>• IP24</li> <li>• Over heat protection</li> </ul>
Element	<ul style="list-style-type: none"> <li>• Aluminium X fin</li> </ul>
Flex Length	<ul style="list-style-type: none"> <li>• 1.2m</li> </ul>
Clearances	<ul style="list-style-type: none"> <li>• 50mm below, 150mm above, 50mm in front.</li> </ul>
Material	<ul style="list-style-type: none"> <li>• Mild Steel</li> </ul>

Codes / Power Output	Size(mm)	Weight(Kg)	
NCH05KWT*	500	420 x 430 x 85	4
NCH07KWT*	750	420 x 510 x 85	4.7
NCH10KWT*	1000	420 x 555 x 85	5
NCH15KWT*	1500	420 x 755 x 85	6.5
NCH20KWT*	2000	420 x 955 x 85	8.5
NCH25KWT*	2500	420 x 1170 x 85	10

Codes / Power Output	Size(mm)	Weight(Kg)	
NEOL06KWT*	600	208 x 1005 x 85	3.5
NEOL08KWT*	800	208 x 1186 x 85	3.9
NEOL10KWT*	1000	208 x 1380 x 85	4.6
NEOL12KWT*	1200	208 x 1548 x 85	5.1
NEOL14KWT*	1400	208 x 1760 x 85	6.5

## WiFi Requirements

Wi-Fi 2.4 GHz, WPA2, 802.11 b/g/n + Bluetooth  
iPhone (iOS 10.0 or higher)  
Android 5.0 or higher

Ensure that there is a good Wifi signal where the heater will be installed.

To connect with the APP, the SSID and password field must be complete. The App will not work on networks without a password.