

Klima WiFi

Overview

Smart WiFi electric dual therm panel heater. Fully ERP LOT20 compliant.

- Programmable thermostat and timer
- WiFi Control
- · Splash proof
- Open window detection
- Presence detection
- Energy optimiser

Specs				
Room Sensors	 Electric Thermostat - accurate to (0.5 °C) range 7-30 °C Presence detection / empty room sensor - Decreases temperature when room is empty 60min = -1°, 90min = -2°, 120min = -3.5°, 38hour = Anti Frost mode Open window detection 			
Manual Control	Complete functionality using control panel			
WiFi Control	Inbult WiFi connectivity Fully programmable with Radialight App App available on IOS and Android stores 2.4ghz WiFi			
Programmer	24 hour 7 day inbuilt timer 3 Heating Modes - "Comfort", "Eco" and "Anti-Frost"			
Display	LCD digital display			
Eco Features	 Open window detection Presence detection Energy optimiser - Lowers energy consumption as room reaches temperature Records energy consumption 			
Installation	• 1 H wall bracket			
Protection	IP24Over heat protection			
Element	Aluminium X fin convectorRadiant element in front panel			
Flex Length	• 1.2m			



Detail			
Guarantee	2 Years (Bodywork and Electronics)		
Manufacturer	Radialight		
Colours	White, Anthracite		

Codes		Size(mm)	Weight(Kg)
KLIMA07WiFi	750w	675 x 504 x 90	6.8
KLIMA10WiFi	1000w	790 x 504 x 90	7.7
KLIMA15WiFi	1500w	1010 x 504 x 90	9.5
KLIMA20WiFi	2000w	1310 x 504 x 90	11.6

WiFi Requirements

Wi-Fi 2,4 GHz, iPhone (IOS 10.0 or higher) Android 5.0 or higher

Ensure that there is a good Wifi signal where the heater will be installed.