



Aetherea

Overview


Digital electric dual therm panel heater with digital controls. Fully ERP LOT20 compliant.

- WiFi and Non WiFi versions
- Programmable thermostat and timer
- Splash proof
- Open window detection
- Presence detection
- Energy optimiser
- Al learning technology





Specs				
Room Sensors	 Electric Thermostat - accurate to (0.5 °C) range 7-30 °C Presence detection / empty room sensor - Decreases temperature when room is empty. 60min = -1°, 90min = -2°, 120min = -3.5°, 38hour = Anti Frost mode Open window detection 			
Programmer	 24 hour 7 day inbuilt timer. 3 Heating Modes - "Comfort", "Eco" and "Anti-Frost" Al self programming. Can create a schedule around your habits 			
Display	LCD digital display			
Eco Features	 Open window detection Presence detection Energy optimiser - Lowers energy consumption as room reaches temperature 			
Installation	• 1 H wall bracket			
Protection	IP24Over heat protection			
Element	Aluminium X fin convector Radiant element in front panel			
Flex Length	• 1.2m			
Clearances	150mm below, 150mm above, 150mm in front.			
Material	Mild Steel			



Detail				
Guarantee	2 Years (Bodywork and Electronics)			
Manufacturer	Radialight			
Colours	White, Black			

Codes		Size(mm)	Weight(Kg)
ATH10	1000w	800 x 450 x 80	7.7
ATH15	1500w	1020 x 450 x 80	9.5